

## **Press Release**

## **Major Specifications**

Steering			LHD / RHD
Number of doors			5
Engine			Petrol
Lingine		<b>-</b>	2.5L Plug-in Hybrid
Drive system			E-Four
DIMENSIONS			E-FOUI
Overall length		mm	4,635
		mm	1,855
Overall width Overall height		mm	1,690
		mm	2,690
Wheelbase Tread	Frant	mm	1,600
	Front	mm	,
Minimum tuming undive	Rear	mm	1,630 5.7
Minimum turning radius Minimum ground clearance		m	190
	nce	mm	190
CAPACITY Continue annuity		200000	Ę
Seating capacity	May values	persons	5
Luggage capacity	Max.volume	litres	1,604
	Rear seatback folded (VDA method)	litres	1,168
	Rear seatback raised (VDA method)	litres	490
Fuel tank capacity		litres	55
Battery capacity		kWh	18.1
ENGINE			A25A-FXS
Туре			
Number of cylinders			4
Number of valves			16
Piston displacement		cm3	2,487
Bore×stroke		mm	87.5 x 103.4
Compression ratio			14.0:1
Maximum output		kW/rpm	136
Maximum torque		Nm/rpm	227
Fuel distribution			Port Injection + Direct Injection
ELECTRIC MOTOR	les e		
Front	Maximum output	kW	134
	Maximum torque	Nm	270
Rear	Maximum output	kW	40
	Maximum torque	Nm	121
TRANSMISSION			
Туре			E-CVT (Automatic)
CHASSIS			
Steering			Rack & pinion
Brakes	Front		Ventilated disc
	Rear		Ventilated disc
Suspensions	Front		MacPherson strut
	Rear		Double wishbone
Tyres Size			235/55R19
WEIGHTS			
Kerb weight		kg	1,940
Gross vehicle weight		kg	2,510
PERFORMANCE			
Maximum speed		km/h	180
EV mode driving range		km	75
ENVIRONMENTAL PERF			
Emission standard compliance			Euro 6d
CO2 emissions (NEDC)		g/km	26
CO2 emissions (WLTP)		g/km	22

All figures are manufacture's data and may vary for each market.

<sup>\*</sup>AC on-board charger capacity (Maximum rated output) is 3.3 kW (Plug-in charge control system for DC charging is not used).